

COWANS

COWANS SHELDON

SHELDON

65T Railway Recovery Cranes



The CCS 65 – 8T, 65 tonnes at 8 metres radius capacity diesel hydraulic railway breakdown crane, two units have been delivered to Sudan Railway Corporation and one is seen recovering a tanker wagon.

This diesel hydraulic breakdown crane includes the latest state of the art hydraulic drives and latest technology for loadguard systems.

factsheet

Over the years we have designed and built heavy duty railway cranes with lifting capacities ranging from 60 to 250 tonnes for many of the worlds leading railway networks.

Today our second to none technology and practical expertise enable us to supply diesel hydraulic cranes including telescopic boom models and diesel electric cranes and the Cowans Sheldon product range now covers the important track maintenance sector.



65T Railway Recovery Cranes

The CCS 65 - 8T is one of the most sophisticated diesel hydraulic railway breakdown cranes to be seen anywhere in the world and incorporates the following innovative features:

- The latest state of the art technology for hydraulic drives allows continuous and smooth control of all movements of the crane at the same time independently and within the diesel hydraulic power unit capacity. Hydraulic control gives self adaptation of the speed to the motor load as well as overload protection.
- Powered swing type outriggers giving a wide variety of propping bases which enhance stability and lifting performance; outriggers incorporate long stroke jacks minimising packing.
- The latest electronic safe load indicator system gives limitation of slew sectors and overload protection.

The Crane may also be provided with the following innovative features:

- A carriage tilting mechanism allowing the crane to self level on canted track thereby maintaining free on rail lifting performance.

- New parabolic spring suspension allowing in-train speeds up to 120 km/h
- Tandem lifting on the main and auxiliary hoist system under safe load indicator system control.

A typical load chart is featured below.

| Radius | Slew Angle 360° | | Slew Angle ±22,5° | |
|--------|-----------------|------------|-------------------|------------|
| | Main Hoist | Aux. Hoist | Main Hoist | Aux. Hoist |
| 4.75 | 65 | | 65 | |
| 6.00 | 65 | 15 | 65 | 15 |
| 7.50 | 65 | 15 | 65 | 15 |
| 8.00 | 58 | 15 | 65 | 15 |
| 10.00 | 40 | 15 | 50 | 15 |
| 12.00 | 30 | 15 | 32 | 15 |
| 14.00 | 24 | 15 | 24 | 15 |

'...designed and built heavy duty railway cranes with lifting capacities ranging from 60 to 250 tonnes...'

COWANS SHELTON



LANGLEY

A Langley Holdings Company

Whilst this information is given in good faith, no warranty or representation is given concerning such information, which must not be taken as establishing any contractual or other commitment binding upon The Clarke Chapman Group Ltd or any of its subsidiary or associated companies.

0504

Cowans Sheldon

Saltmeadows Road, Gateshead,
Tyne & Wear, NE8 1SW, England
Tel +44 (0)191 477 2271
Fax +44 (0)191 490 7603

www.cowanssheldon.co.uk

A division of The Clarke Chapman Group Ltd