<u> COWANS SHELDON</u>

TOWAN5

140T Railway Recovery Cranes





The CCS 140 – 10T, 140 tonnes at 10 metres radius capacity diesel hydraulic railway breakdown crane, ten units have

been delivered to INDIAN RAILWAYS since 1988. One is seen during commissioning tests in India.

factsheet

Over the years we have designed and built heavy duty railway cranes with lifting capacities ranging from 60 to 250 tonnes for many of the worlds leading railway networks.

Today our second to none technology and practical expertise enable us to supply diesel hydraulic cranes including telescopic boom models and diesel electric cranes and the Cowans Sheldon product range now covers the important track maintenance sector.



140T Railway Recovery Cranes

The CCS 140 - 10T is one of the most sophisticated diesel hydraulic railway breakdown cranes to be seen anywhere in the world and incorporates the following innovative features:

- The latest state of the art technology for hydraulic drives allows continuous and smooth control of all movements of the crane at the same time independently and within the diesel hydraulic power unit capacity. Hydraulic control gives self adaptation of the speed to the motor load as well as overload protection.
- Powered swing type outriggers giving a wide variety of propping bases which enhance stability and lifting performance; outriggers incorporate long stroke jacks minimising packing.
- The latest electronic safe load indicator system gives limitation of slew sectors and overload protection.

The Crane may also be provided with the following innovative features:

 A carriage tilting mechanism allowing the crane to self level on canted track thereby maintaining free on rail lifting performance.

- New parabolic spring suspension allowing in-train speeds up to 120 km/h
- Tandem lifting on the main and auxiliary hoist system under safe load indicator system control.

A typical load chart is featured below.

	Slew Angle 360°		Slew Angle ±30°	
	Propped Load in Tonnes		Propped Load in Tonnes	
Radius	Main Hoist	Aux. Hoist	Main Hoist	Aux. Hoist
5.5	140		140	
7.0	140	25	140	25
9.0	101	25	140	25
10.0	86	25	140	25
11.0	74	25	130	25
13.0	58	25	105	25
15.0	47	25	85	25
16.0	42	25	70	25
19.0		25		

'...designed and built heavy duty railway cranes with lifting capacities ranging from 60 to 250 tonnes...'





Whilst this information is given in good faith, no warranty or representation is given concerning such information, which must not be taken as establishing any contractual or other commitment binding upon The Clarke Chapman Group Ltd or any of its subsidiary or associated companies.

0504

Cowans Sheldon

Saltmeadows Road, Gateshead, Tyne & Wear, NE8 1SW, England Tel +44 (0)191 477 2271 Fax +44 (0)191 490 7603